

## XTS Shear



Equipped with a hydraulic speed valve improves servicibility and minimizes stress on other critical components. Our improved jaw geometry for easier material pick up and reduced wear from ground contact.

### XTS Specifications

		XTS17	XTS30	XTS50	XTS50M
Excavator Class	lbs	3300-5500	6600-11000	8800-15500	8800-15500
	ton	1.5~2.5	3~5	4~7	4~7
Weight	lbs	451	767	970	1031
	ton	0.20	0.34	0.44	0.46
MAX. JAW OPENING	inch	7.0	10.2	11.8	11.8
	mm	178	259	300	300

<b>MAX. JAW Depth</b>	<b>inch</b>	11.6	14.4	15.5	15.5
	<b>mm</b>	295	366	394	394
<b>Cutting Force</b>	<b>lbs</b>	48,500	85,900	100,000	100,000
	<b>ton</b>	22.0	39.0	45.4	45.4
<b>Jaw Maximum Pressure</b>	<b>psi</b>	2,987	2,987	3,270	3,270
	<b>bar</b>	206	206	225	225
<b>Operating Flow</b>	<b>gpm</b>	5	10	15	15
	<b>lpm</b>	20	38	57	57
<b>Steel Cutting Capacity</b>			<b>I-beam (HxWxT 1xT2)</b>		<b>inch</b>
					<b>mm</b>
			<b>H-beam (HxWxT 1xT2)</b>		<b>inch</b>
					<b>mm</b>
			<b>Pipe (diameter x T)</b>		<b>inch</b>
					<b>mm</b>
			<b>Cylinder bar (diameter)</b>		<b>inch</b>
					<b>mm</b>