

XTVC VCOMPACTOR



XTVC Specifications

			XTVC50	XTVC140	XTVC200	XTVC300
WEIGHT	Adapter Type	lb				
		kg				
Direct Type		lb	838	1,433	2,094	2,535
		kg	380	650	950	1150
Compaction force		lb				
		ton	5	7	13	15
Frequency		rpm	600-3000	600-2000		
Operating Pressure		psi				
		bar	100-150	150-200	150-210	150-210
Oil Flow Range		CC/Rev.	30	63	80	80/90
Dimension	Overall Length	inch	36	45	49	53
		mm	915	1145	1250	1350
	Overall Width	inch				
		mm	530	700	850	950
Recommended Carrier Weight		lb				
		ton	4 - 6	9 - 13	18 - 22	28 - 32

The above specification may be changed without prior notice for product improvement.

			XTVC50 E	XTVC70 E	XTVC150 E	XTVC230 E	XTVC300 E
WEIGHT	Adapter Type	lb	1,190	1,420	1,490	1,609	1,609
		kg	540	644	676	730	730
Direct Type		lb	1,656	1,903	2,033	2,299	2,407
		kg	751	863	922	1043	1092
Compaction force		lb	8,818	13,228	16,535	33,069	33,069
		ton	4	6	8	15	15
Frequency		rpm	1800	1800	1800	2000	2000
Operating Pressure		psi	1450-2466	1740-2611	2176-3046	2466-3191	2466-3191
		bar	100-170	120-180	150-210	170-220	170-220
Oil Flow Range		CC/Rev.	45-65	50-70	80-110	120-170	150-200
Dimension	Overall Length	inch	35	37	46	53	53
		mm	900	950	1160	1350	1350
	Overall Width	inch	22	22	28	28	35
		mm	550	550	700	700	900
Recommended Carrier Weight		lb	8810-11020	13230-22050	28660-35270	39680-55115	61730-72750
		ton	4 - 5	6 - 10	13 - 16	18 - 25	28 - 33

The above specification may be changed without prior notice for product improvement.