

XTWG mini Wood Grapple



- Constructed with high strength and abrasion resistant materials.
- All pin holes are heat treated.
- Equipped with a stop bar for stability during maintenance.
- Internal hoses protected from environment.
- 360 hydraulic motor rotation and reverse mode.
- Wide range of models to fit your excavator.

XTWG Specifications

		XTWG10	XTWG17	XTWG30	XTWG50
WEIGHT	lb	229.28	297.62	555.56	705.48
	kg	104.00	135.00	252.00	320.00
MIN	inch	0.00	0.00	0.00	0.00
	mm				

MAX	inch	31.50	37.01	46.06	50.39
	mm	800.00	940.00	1170.00	1280.00
H	inch	33.07	37.01	48.03	41.34
	mm	840.00	940.00	1220.00	1050.00
H1	inch	38.98	43.70	55.91	33.46
	mm	990.00	1110.00	1420.00	850.00
Open & Close Pressure	psi	2417.97	2986.90	2986.90	3342.49
	kgf/cm ²	170.00	210.00	210.00	235.00
Rotator Pressure	psi	0.00	0.00	0.00	0.00
	kgf/cm ²	-	-	-	-
Motor Drain piping installation		Semi-Automatic			
Recommended Carrier Weight	Lbs	1800-3300	3808-4480	6720-8960	11020-20160
	Ton	0.8-1	1.7-2	3-4	5-9